

Single Gas Valves

Solenoid gas valve, normally closed VE400AA



VE400AA



Class "A" AC powered, Safety Shutoff Solenoid Gas Valve.

For pilot and small burner applications in gas power burners, gas boilers, ovens, furnaces and other gas consuming appliances.

Gas valve type	AC powered, non regulated ON/OFF normally closed, fast opening.
Media	natural gas, propane, air.
Materials	brass body for 1/4" version, aluminium body for others.
Approvals	CE (EN161), GOST, AGA
Pipe connection	Internal thread as per ISO 7/1 (Rp)
Threads type	BSP
Maximum opening time	1 s
Maximum closing time	1 s
Ambient temperature	-15 ... 60 °C
Protection class	IP65
Electrical connection	DIN plug

220...240 Vac versions

Valve dimension	Max. operating pressure mbar	Type
Rp 1/4	500	VE408AA1007
Rp 3/8	360	VE410AA1003
Rp 1/2	360	VE415AA1008
Rp 3/4	200	VE420AA1001

110 Vac versions

Valve dimension	Max. operating pressure mbar	Type
Rp 1/4	500	VE408AA1015
Rp 3/8	360	VE410AA1011
Rp 1/2	360	VE415AA1016
Rp 1/2	200	VE420AA1019